

KISSLING | KISSLING Series 30

TE Internal #: K1004425 General Purpose Power Relay, Bistable, 2 Coils, Polarized, .067 W Coil, 7.8 – 8.4 ohm Coil Resistance, KISSLING Series 30, Power Relays

View on TE.com >



Relays & Contactors > Relays > Power Relays > Power Relay, 200A, Standard, Bistable, 2 Coils, Polarized



Relay Type: General Purpose Power Relay

Coil Magnetic System: Bistable, 2 Coils, Polarized

Coil Power Rating DC: .067 W

Coil Resistance: $7.8 - 8.4 \Omega$

Coil Special Features: Coil Suppression Diode

All Power Relay, 200A, Standard, Bistable, 2 Coils, Polarized (8)

Features

Product Type Features

Relay Type

General Purpose Power Relay

Configuration Features

Coil Special Features	Coil Suppression Diode	
Contact Arrangement	1 Form X SPST-NO-DM	
Contact Number of Poles	1	
Electrical Characteristics		
Coil Power Rating DC	.067 W	
Coil Resistance	7.8 – 8.4 Ω	
Coil Voltage Rating	18 VDC, 32 VDC	
Contact Current Rating	200 A	
Contact Voltage Rating	24 VDC	
Contact Features		
Contact Material	Ag Alloy	
Termination Features		
Relay Connection Type	Terminals	

30-213-12

General Purpose Power Relay, Bistable, 2 Coils, Polarized, .067 W Coil, 7.8 – 8.4 ohm Coil Resistance, KISSLING Series 30, Power Relays



Terminal Configuration	Screw Terminals	
Mechanical Attachment		
Product Mounting Feature Type	Flange with Mounting Holes	
Product Mount Type	Panel	
Dimensions		
Product Width	60 mm[2.36 in]	
Product Length	78 mm[3.07 in]	
Product Height	90 mm[3.54 in]	
Operation/Application		
Coil Magnetic System	Bistable, 2 Coils, Polarized	
Packaging Features		
Packaging Method	Carton	
Other		
Contact Current Class	200 A	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Yet Reviewed	
EU ELV Directive 2000/53/EC	Not Yet Reviewed	
China RoHS 2 Directive MIIT Order No 32, 2016	Not reviewed for China RoHS compliance	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Not Yet Reviewed	
Halogen Content	Not Yet Reviewed for halogen content	
Solder Process Capability	Not reviewed for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the

30-213-12

General Purpose Power Relay, Bistable, 2 Coils, Polarized, .067 W Coil, 7.8 – 8.4 ohm Coil Resistance, KISSLING Series 30, Power Relays



product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # CAT-AL6-KSPR29200 Power Relay, 200A, Standard, Monostable, DC



TE Part # CAT-AL6-KSPR30200 Power Relay, 200A, Standard, Bistable, 2 Coils, Polarized

Also in the Series | KISSLING Series 30



Power Relays(37)

Customers Also Bought

		TE TE	E
TE Part #K1156392	TE Part #K1011766	TE Part #K1060041	TE Part #K1149808
Battery Disconnector, 500A, 2 Pole	Relay 29-214-11	Relay 30-311-12	Push button switch TS-221-SW11 908

TE Part #K1147050 Relay 28-311-99-900

Documents

Product Drawings

C For support call+1 800 522 6752

30-213-12

General Purpose Power Relay, Bistable, 2 Coils, Polarized, .067 W Coil, 7.8 – 8.4 ohm Coil Resistance, KISSLING Series 30, Power Relays



Relay 30-213-12

German

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_30-213-12_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_30-213-12_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_30-213-12_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages KISSLING SINGLE POLE BI-STABLE RELAYS Series 30 / 200A

English